

“DOUSED FIRE” DFW-200 for WOOD

PRODUCTS DATA SHEET

DESCRIPTION:

“DOUSED FIRE” DFW-200 PRODUCT IS USEFUL FOR IMPARTING FLAME RETARDANCY TO RAW/VIRGIN WOOD, SUCH AS PLYWOOD, MDF, SLEEPER WOOD ETC, DFW-200 IS NON-HAZARDOUS AND ENVIRONMENT FRIENDLY, IT DOES NOT EFFECT ANY PHYSICAL PROPERTIES OF THE WOOD, IT HAS AN INTUMESCENT / CHAR FORMING PROPERTY, IT GIVES A LONG LIFE DUE TO THE CHEMICAL BONDING PROPERTIES PROVIDED IT IS STORED IN A CLOSED CONTAINER.

SPECIFICATION:

- 1) COLOUR: PALE BROWN CLEAR LIQUID.
- 2) PH: 7-8.
- 3) SOLUBILITY: SOLUBLE IN WATER.
- 4) SOLID CONTENT: 40% +/- 2%.

DOSAGE: 500 grms of Product to be diluted in 500 grms of water. (50:50).

APPLICATION METHOD:

- 1) DFW-200 CAN BE APPLIED ON WOOD BY BRUSH, SPRAY OR ROLLER METHOD.
- 2) APPLY 4 COATS OF DFW-200 FOR ACHIEVING 90 MINUTES RATING

PACKING:

AVAILABLE IN 25 / 50 & 200 KILOS HDPE DRUMS.

