## <u>UNIVERSAL ENTERPRISES</u> IFIIRIE-X PIRIMIE

INTUMSCENT PAINT PRIMER



## TDS/FXPRIME/020513

## **Technical Data Sheet**

Product Description:	A high performance, high build, solvent based, fire retardant intumescent primer, designed as a universal product to be used on Walls, Gypsum Partitions and Wooden structures, Gypsum Boards, False ceilings and structural steel requiring protection from fire hazard. Typically applied on site, <b>Fire-X Prime</b> will act as a primer for application of Fire X 301 and will increase its coverage, thereby reducing the cost.
	from fire hazard. Typically applied on site, <b>Fire-X Prime</b> will act as a primer for application of Fire X 301 and will increase

Physical Properties :	Colour	Off. White
<b>Properties :</b>	Viscosity (B4)	80-85 sec
	Solid Content	
	Specific gravity	1.1+/- 0.03

Thickness:	Thickness of a single coat of <b>FIRE-X PRIME</b> is around <b>30-</b>
	40µ.

Coverage:	Theoretically,1ltr of <b>FIRE-X PRIME</b> covers up to <b>50-55 sqft.</b>
-----------	---

Drying time:	Surface dry 45mins
i B	Hard dry 3 hrs

Surface preparation:	All surfaces to be coated, should be clean, dry and free from loose particles, dirt, grease and other foreign materials and contamination.
-------------------------	--

Application:	<b>FIRE-X PRIME</b> is a one component coating and should be mixed thoroughly with a <b>power agitator</b> . Dilution of upto 20% if required should be done only with Wathin 7. This product is designed for only roller <b>application</b> .

<b>Storage:</b> Typical shelf life of <b>FIRE-X PRIME</b> is 3 months.
--

CONTACT: Mr. Ashit Prajapati Sales office: 56/62, Chandabhoy building, Mezzanine floor, Mangaldas Road, Lohar Chawl, Mumbai – 400 002. Sales Off: +91 22 22087499 Cell: 7021889118 / 7738290786

ashitp@unient.in www.unient.in