



UNIVERSAL ENTERPRISES

PREVENTION | PROTECTION | SAFETY



7021889118

7738290786



022-26718965

022-49645519



ashitp@unient.in



www.unient.in

PRODUCT DATA SHEET

“DOUSED FIRE” DFWL-201

FOR LAMINATED WOOD LIKE SUNMICA, FORMICA & POLISHED SURFACES.

DESCRIPTION:

“DOUSED FIRE” DFWL-201 PRODUCT IS USEFUL FOR IMPARTING FLAME RETARDANCY TO TREATED/LAMINATED WOOD, SUCH AS MELAMINE POLISHED SURFACE, LAMINATED WOOD, SUNMICA / FORMICA WOOD ETC, DFWL-201 IS NON-HAZARDOUS AND ENVIRONMENT FRIENDLY, IT DOES NOT AFFECT ANY PHYSICAL PROPERTIES OF THE WOOD, IT HAS AN INTUMESCENT / CHAR FORMING PROPERTY, IT GIVES A LONG LIFE DUE TO THE CHEMICAL BONDING PROPERTIES PROVIDED. IT IS TO BE STORED IN A CLOSED CONTAINER AWAY FROM SUNLIGHT IN SHADE.

SPECIFICATION:

- 1) COLOUR: PALE BROWN CLEAR LIQUID.
- 2) PH: 7-8.
- 3) SOLUBILITY: SOLUBLE IN WATER.
- 4) SOLID CONTENT: 40% +/- 2%.

USAGE: PRODUCT IS READY TO USE AND DOES NOT NEED ANY DILUTION OR PROCESSING,

APPLICATION METHOD:

- 1) DFWL-201 CAN BE APPLIED ON WOOD BY BRUSH, SPRAY OR ROLLER METHOD.
- 2) APPLY 4 COATS OF DFWL-201 FOR ACHIEVING 120 MINUTES RATING

PACKING:

AVAILABLE IN 25 / 50 & 200 KILOS HDPE DRUMS.